


Pozicija	Kol.	Opis
	1	<b>JPA 4-47 PT-H A-A-BBVP</b>  <p>Opozorilo! Slika proizvoda je simboli na</p> <p>Št. proizvoda: <a href="#">98946108</a></p> <p>The JPA PT is an pressure booster unit consisting of a JPA pump, a pressure switch, a pressure gauge and a diaphragm tank. The pressure switch automatically starts the pump according to demand. The diaphragm tank ensures a controlled pressure in the water supply and thereby limits the switching frequency of the pump in case of low water consumption or leakage loss. Furthermore, the diaphragm tank increases system comfort by compensating for pressure drops when a tap is opened, and finally it reduces problems with water hammer in the pipework.</p> <p><b>Teko ina:</b> rpana teko ina: Voda Razpon temperature teko ine: 0 .. 35 °C Liquid temperature during operation: 20 °C Specifi na teža: 998.2 kg/m3</p> <p><b>Tehni ni podatki:</b> Primarno tesnilo osi: BBVP Odobritive na napisni tablici: CE,EAC Toleranca krivulje: ISO9906:2012 3B</p> <p><b>Materiali:</b> Ohišje rpalke: Cast iron EN 1561 EN-GJL-200 Teka : COMPOSITE</p> <p><b>Montaža:</b> Razpon temperature okolice: -10 .. 40 °C Maks. delovni tlak: 8 bar Sesalni priklju ek rpalke: G 1 Tla ni priklju ek rpalke: G 1</p> <p><b>Elektri ni podatki:</b> Vhodna mo - P1: 850 W C delovanje: 13 µF Omrežna frekvenca: 50 Hz Nominalna napetost: 1 x 220-240 V Nominalni tok: 3.8 A Velikost kondenzatorja - v teku: 13 µF/450 V Razred zaš ite (IEC 34-5): IP44 Izolacijski razred (IEC 85): F Dolžina kabla: 2 m Tip kablskega priklju ka: SCHUKO</p> <p><b>Posoda:</b></p>

Pozicija	Kol.	Opis
		Volumen tla ne posode: 20 l
		<b>Drugo:</b>
		Neto teža: 17 kg
		Bruto teža: 20 kg